


www.bolarus.com.pl e-mail: office@bolarus.com.pl tel. +48 14 61 49 300 fax +48 14 61 49 301; +48 14 61 49 303




## Type: Cooling cabinet



S-147 S





## Technical description

Art. No.

DimensionLengthWidthHeightInternal14408602020internal13206951505Capacity::195 [kg]Loading::300 [kg]Loading::0 [kg]Length0 [kg]Lengterure range::Ervice conditions::1.6. +43 [°C] 60% HR.Rate dower::Editoring power::2.00 [W]Cooling power::2.01 [Cooling power::2.02 [W]Cooling power::2.02 [W]Cooling power::2.05 [VH2]Dower supply::2.35 [kWh/24h]Power supply::2.45 [velocinal not with digital display of temperature9 adjustable feet, range 0-50 nm1.40 at least circulatio9 automatic fan switch1.40 at least circulatio9 automatic fan switch1.50 [manuel display]9 at least circulatio9 at least circulatio9 at least circulatio	Cooling cabinet S-147 S					
ImmaExternal14408602020Internal13206951505Capacity:195 [kg]Loading:300 [kg]No. of shelves:6 piecesMax loading for shelf:30 [kg]Temperature range: $+1+10$ [°C]Service conditions: $+16+43$ [°C] 60% HRRated power:550 [W]Cooling power:620 [W]Refrigerant:R-404a or R-134aPower requirement:3,53 [kWh/24h]Power supply:235/50 [V/Hz]No. of doors:2Version:• external white painted (by poulder)• internal made of aluminium (mat)• eological polyurethane insulation, width 60 mm• easily replaceable door gasket• electronic control with digital display of temperature• automatic defrost and evaporation system• adjustable feet, range 0-50 mm• fan air circulation• door lock• automatic fan switchStandard outfit:• 12 shelf guides• manual descriptionOptional outfit:• additional metal coated shelves• shelf made of INOX• hooks for meat products• sound signalling• foot pedal for door opening• inside light• temperature recorderOptional execution:• static air circulation• foot pedal for door opening• inside light• temperature recorderOptional execution:• static air circulation <td>Dimension</td> <td></td> <td>Length</td> <td>Width</td> <td>Height</td>	Dimension		Length	Width	Height	
Internal13206951505Capacity:1400 [dm³]Bare weight:195 [kg]Loading:300 [kg]No. of shelves:6 piecesMax loading for shelf:30 [kg]Temperature range:+1 +10 [°C]Service conditions:+16 +43 [°C] 60% HRRated power:620 [W]Cooling power:620 [W]Refrigerant:R-404a or R-134aPower requirement:3,53 [kWh/24h]Power supply:235/50 [V/Hz]No. of doors:2Version:• external white painted (by poulder)• internal made of aluminum (mat)• ecological polyurethane insulation, width 60 mm• easily replaceable door gasket• electronic control with digital display of temperature• automatic defrost and evaporation system• adjustable feet, range 0-50 mm• fan air circulation• door lock• automatic fan switchStandard outfit:• anaul descriptionOptional outfit:• additional metal coated shelves• shelf made of INOX• hooks for meat products• sound signalling• foot pedal for door opening• inside light• temperature recorderOptional execution:• static air circulation		External				
Bare weight:195 [kg]Loading:300 [kg]No. of shelves:6 piecesMax loading for shelf:30 [kg]Temperature range:+1+10 [°C]Service conditions:+16+43 [°C] 60% HRRated power:620 [W]Cooling power:620 [W]Refrigerant:R-404a or R-134aPower requirement:3,53 [kWh/24h]Power supply:235/50 [V/Hz]No. of doors:2Version:- external white painted (by poulder)- internal made of aluminium (mat)- ecological polyurethane insulation, width 60 mm- eadjustable feet, range 0-50 mm- fan air circulation- door lock- automatic defrost and evaporation system- adjustable feet, range 0-50 mm- fan air circulation- door lock- automatic fan switchStandard outfit:- 6 metal coated shelves- ghelf guides- manual descriptionOptional outfit:- additional metal coated shelves- shelf made of INOX- hooks for meat products- sound signalling- foot pedal for door opening- inside light- temperature recorderOptional execution:- static air circulation	[]	Internal				
Bare weight:195 [kg]Loading:300 [kg]No. of shelves:6 piecesMax loading for shelf:30 [kg]Temperature range:+1+10 [°C]Service conditions:+16+43 [°C] 60% HRRated power:620 [W]Cooling power:620 [W]Refrigerant:R-404a or R-134aPower requirement:3,53 [kWh/24h]Power supply:235/50 [V/Hz]No. of doors:2Version:- external white painted (by poulder)- internal made of aluminium (mat)- ecological polyurethane insulation, width 60 mm- eadjustable feet, range 0-50 mm- fan air circulation- door lock- automatic defrost and evaporation system- adjustable feet, range 0-50 mm- fan air circulation- door lock- automatic fan switchStandard outfit:- 6 metal coated shelves- ghelf guides- manual descriptionOptional outfit:- additional metal coated shelves- shelf made of INOX- hooks for meat products- sound signalling- foot pedal for door opening- inside light- temperature recorderOptional execution:- static air circulation					I	
Loading: 300 [kg] No. of shelves: 6 pieces Max loading for shelf: 30 [kg] Temperature range: +1+10 [°C] Service conditions: +16+43 [°C] 60% HR Rated power: 620 [W] Refrigerant: R-404a or R-134a Power requirement: 3,53 [kWh/24h] Power supply: 235/50 [V/Hz] No. of doors: 2 Version: - external white painted (by poulder) - internal made of aluminium (mat) - ecological polyurethane insulation, width 60 mm - easily replaceable door gasket - electronic control with digital display of temperature - automatic defrost and evaporation system - adjustable feet, range 0-50 mm - fan air circulation - door lock - automatic fan switch Standard outfit: - 6 metal coated shelves (dimension of shelf: 530 x 650 mm) - 12 shelf guides - manual description Optional outfit: - additional metal coated shelves - shelf made of INOX - hooks for meat products - sound signalling - foot pedal for door opening - inside light - temperature recorder Optional execution: - static air circulation - static air circulation - tatic air circulation - tatic air circulation - static air circulation - static air circulation - static air circulation - another finishing materials for example AISI 430	Capacity:		1400 [dm <sup>3</sup> ]			
No. of shelves:6 piecesMax loading for shelf:30 [kg]Temperature range:+1 +10 [°C]Service conditions:+16 +43 [°C] 60% HRRated power:550 [W]Cooling power:620 [W]Refrigerant:R-404 aor R-134aPower requirement:3,53 [kWh/24h]Power supply:235/50 [V/Hz]No. of doors:2Version: external white painted (by poulder)- internal made of aluminium (mat)- ecological polyurethane insulation, width 60 mm- easily replaceable door gasket- electronic control with digital display of temperature- automatic defrost and evaporation system- adjustable feet, range 0-50 mm- fan air circulation- door lock- automatic fan switchStandard outfit:- of metal coated shelves(dimension of shelf: 530 x 650 mm)- 12 shelf guides- manual descriptionOptional outfit:- additional metal coated shelves- shelf made of INOX- hooks for meat products- sound signalling- fot pedal for door opening- inside light- temperature recorderOptional execution:- static air circulation- ottatic air circulation	Bare weight:		195 [kg]			
Max loading for shelf: 30 [kg] Temperature range: +1+10 [°C] Service conditions: +16+43 [°C] 60% HR Rated power: 550 [W] Cooling power: 620 [W] Refrigerant: R-404a or R-134a Power requirement: 3,53 [kWh/24h] Power supply: 235/50 [V/Hz] No. of doors: 2 Version: - external white painted (by poulder) - internal made of aluminium (mat) - ecological polyurethane insulation, width 60 mm - easily replaceable door gasket - electronic control with digital display of temperature - automatic defrost and evaporation system - adjustable feet, range 0-50 mm - fan air circulation - door lock - automatic fan switch Standard outfit: - of metal coated shelves (dimension of shelf: 530 x 650 mm) - 12 shelf guides - manual description Optional outfit: - additional metal coated shelves - shelf made of INOX - hooks for meat products - sound signalling - foot pedal for door opening - inside light - temperature recorder Optional execution: - static air circulation - sound signalling - sound signalling - foot pedal for door opening - - static air circulation - static air circulation - another finishing materials for example AISI 430	Loading:		300 [kg]			
Temperature range:       +1+10 [°C]         Service conditions:       +16+43 [°C] 60% HR         Rated power:       520 [W]         Cooling power:       620 [W]         Refrigerant:       R-404a or R-134a         Power requirement:       3,53 [kWh/24h]         Power supply:       235/50 [V/Hz]         No. of doors:       2         Version:       -         - external white painted (by poulder)         - internal made of aluminium (mat)         - ecological polyurethane insulation, width 60 mm         - easily replaceable door gasket         - electronic control with digital display of temperature         - automatic defrost and evaporation system         - adjustable feet, range 0-50 mm         - fan air circulation         - door lock         - automatic fan switch         Standard outfit:         - 6 metal coated shelves         (dimension of shelf: 530 x 650 mm)         - 12 shelf guides         - manual description         Optional outfit:         - additional metal coated shelves         - shelf made of INOX         - hooks for meat products         - sound signalling         - foot pedal for door opening         - inside ligh	No. of shelves:		6 pieces			
Service conditions: +16 +43 [°C] 60% HR Rated power: 550 [W] Cooling power: 620 [W] Refrigerant: R-404a or R-134a Power requirement: 3,53 [KWh/24h] Power supply: 235/50 [V/Hz] No. of doors: 2 Version: - external white painted (by poulder) - internal made of aluminium (mat) - ecological polyurethane insulation, width 60 mm - easily replaceable door gasket - electronic control with digital display of temperature - automatic defrost and evaporation system - adjustable feet, range 0-50 mm - fan air circulation - door lock - automatic fan switch Standard outfit: - 6 metal coated shelves (dimension of shelf: 530 x 650 mm) - 12 shelf guides - manual description Optional outfit: - additional metal coated shelves - shelf made of INOX - hocks for meat products - sound signalling - foot pedal for door opening - inside light - temperature recorder Optional execution: - static air circulation - static air circulation	•					
Rated power:550 [W]Cooling power:620 [W]Refrigerant:R-404a or R-134aPower requirement:3,53 [kWh/24h]Power supply:235/50 [V/Hz]No. of doors:2Version:- external white painted (by poulder)- internal made of aluminium (mat)- ecological polyurethane insulation, width 60 mm- easily replaceable door gasket- electronic control with digital display of temperature- automatic defrost and evaporation system- adjustable feet, range 0-50 mm- fan air circulation- door lock- automatic fan switchStandard outfit:- 6 metal coated shelves(dimension of shelf: 530 x 650 mm)- 12 shelf guides- manual descriptionOptional outfit:- additional metal coated shelves- shelf made of INOX- hooks for meat products- sound signalling- foot pedal for door opening- inside light- temperature recorderOptional execution:- static air circulation	Temperature range:					
Cooling power:       620 [W]         Refrigerant:       R-404a or R-134a         Power requirement:       3,53 [kWh/24h]         Power supply:       235/50 [V/Hz]         No. of doors:       2         Version:       -         - external white painted (by poulder)       -         - internal made of aluminium (mat)       -         - ecological polyurethane insulation, width 60 mm       -         - easily replaceable door gasket       -         - electronic control with digital display of temperature       -         - automatic defrost and evaporation system       -         - adjustable feet, range 0-50 mm       -         - fan air circulation       -         - door lock       -         - automatic fan switch       -         Standard outfit:       -         - 6 metal coated shelves       -         (dimension of shelf: 530 x 650 mm)       -         - 12 shelf guides       -         - manual description       -         Optional outfit:       -         - additional metal coated shelves       -         - shelf made of INOX       -         - hooks for meat products       -         - sound signalling       -				60% HR		
Refrigerant: R-404a or R-134a   Power requirement: 3,53 [kWh/24h]   Power supply: 235/50 [V/Hz]   No. of doors: 2   Version:   - external white painted (by poulder)   - internal made of aluminium (mat)   - ecological polyurethane insulation, width 60 mm   - easily replaceable door gasket   - electronic control with digital display of temperature   - automatic defrost and evaporation system   - adjustable feet, range 0-50 mm   - fan air circulation   - door look   - automatic fan switch   Standard outfit:   - 6 metal coated shelves   (dimension of shelf: 530 x 650 mm)   - 12 shelf guides   - manual description   Potional outfit: - sound signalling - foot pedal for door opening - inside light - temperature recorder Optional execution: - static air circulation - another finishing materials for example AISI 430	•					
Power requirement::       3,53 [kWh/24h]         Power supply:       235/50 [V/Hz]         No. of doors:       2         Version:       -         - external white painted (by poulder)       -         - internal made of aluminium (mat)       -         - ecological polyurethane insulation, width 60 mm       -         - easily replaceable door gasket       -         - electronic control with digital display of temperature       -         - automatic defrost and evaporation system       -         - adjustable feet, range 0-50 mm       -         - fan air circulation       -         - door lock       -         - automatic fan switch       -         Standard outfit:       -         - 6 metal coated shelves       -         (dimension of shelf: 530 x 650 mm)       -         - 12 shelf guides       -         - manual description       -         Optional outfit:       -         - additional metal coated shelves       -         - shelf made of INOX       -         - hooks for meat products       -         - sound signalling       -         - foot pedal for door opening       -         - inside light       -		er:		.,		
Power supply:       235/50 [V/Hz]         No. of doors:       2         Version:       2         - external white painted (by poulder)	•					
No. of doors: 2 Version: • external white painted (by poulder) • internal made of aluminium (mat) • ecological polyurethane insulation, width 60 mm • easily replaceable door gasket • electronic control with digital display of temperature • automatic defrost and evaporation system • adjustable feet, range 0-50 mm • fan air circulation • door lock • automatic fan switch Standard outfit: • 6 metal coated shelves (dimension of shelf: 530 x 650 mm) • 12 shelf guides • manual description Optional outfit: • additional metal coated shelves • shelf made of INOX • hooks for meat products • sound signalling • foot pedal for door opening • inside light • temperature recorder Optional execution: • static air circulation • another finishing materials for example AISI 430	•		· -	J		
Version:         - external white painted (by poulder)         - internal made of aluminium (mat)         - ecological polyurethane insulation, width 60 mm         - easily replaceable door gasket         - electronic control with digital display of temperature         - automatic defrost and evaporation system         - adjustable feet, range 0-50 mm         - fan air circulation         - door lock         - automatic fan switch         Standard outfit:         - 6 metal coated shelves         (dimension of shelf: 530 x 650 mm)         - 12 shelf guides         - manual description         Optional outfit:         - additional metal coated shelves         - shelf made of INOX         - hooks for meat products         - sound signalling         - foot pedal for door opening         - inside light         - temperature recorder         Optional execution:         - static air circulation						
<ul> <li>external white painted (by poulder)</li> <li>internal made of aluminium (mat)</li> <li>ecological polyurethane insulation, width 60 mm</li> <li>easily replaceable door gasket</li> <li>electronic control with digital display of temperature</li> <li>automatic defrost and evaporation system</li> <li>adjustable feet, range 0-50 mm</li> <li>fan air circulation</li> <li>door lock</li> <li>automatic fan switch</li> </ul> Standard outfit: <ul> <li>6 metal coated shelves</li> <li>(dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> </ul> Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>	NO. 01 00015:		4			
<ul> <li>external white painted (by poulder)</li> <li>internal made of aluminium (mat)</li> <li>ecological polyurethane insulation, width 60 mm</li> <li>easily replaceable door gasket</li> <li>electronic control with digital display of temperature</li> <li>automatic defrost and evaporation system</li> <li>adjustable feet, range 0-50 mm</li> <li>fan air circulation</li> <li>door lock</li> <li>automatic fan switch</li> </ul> Standard outfit: <ul> <li>6 metal coated shelves</li> <li>(dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> </ul> Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>	Version					
<ul> <li>internal made of aluminium (mat)</li> <li>ecological polyurethane insulation, width 60 mm</li> <li>easily replaceable door gasket</li> <li>electronic control with digital display of temperature</li> <li>automatic defrost and evaporation system</li> <li>adjustable feet, range 0-50 mm</li> <li>fan air circulation</li> <li>door lock</li> <li>automatic fan switch</li> </ul> Standard outfit: <ul> <li>of metal coated shelves</li> <li>(dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> </ul> Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>		e painted (by por	ılder)			
<ul> <li>ecological polyurethane insulation, width 60 mm</li> <li>easily replaceable door gasket</li> <li>electronic control with digital display of temperature</li> <li>automatic defrost and evaporation system</li> <li>adjustable feet, range 0-50 mm</li> <li>fan air circulation</li> <li>door lock</li> <li>automatic fan switch</li> </ul> Standard outfit: <ul> <li>6 metal coated shelves</li> <li>(dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> </ul> Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>						
<ul> <li>easily replaceable door gasket</li> <li>electronic control with digital display of temperature</li> <li>automatic defrost and evaporation system</li> <li>adjustable feet, range 0-50 mm</li> <li>fan air circulation</li> <li>door lock</li> <li>automatic fan switch</li> </ul> Standard outfit: <ul> <li>6 metal coated shelves</li> <li>(dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> </ul> Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>						
<ul> <li>electronic control with digital display of temperature</li> <li>automatic defrost and evaporation system</li> <li>adjustable feet, range 0-50 mm</li> <li>fan air circulation</li> <li>door lock</li> <li>automatic fan switch</li> </ul> Standard outfit: <ul> <li>6 metal coated shelves</li> <li>(dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> </ul> Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>						
<ul> <li>automatic defrost and evaporation system</li> <li>adjustable feet, range 0-50 mm</li> <li>fan air circulation</li> <li>door lock</li> <li>automatic fan switch</li> </ul> Standard outfit: <ul> <li>6 metal coated shelves</li> <li>(dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> </ul> Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>another finishing materials for example AISI 430</li> </ul>						
<ul> <li>adjustable feet, range 0-50 mm</li> <li>fan air circulation</li> <li>door lock</li> <li>automatic fan switch</li> </ul> Standard outfit: <ul> <li>6 metal coated shelves</li> <li>(dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> </ul> Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>						
<ul> <li>fan air circulation</li> <li>door lock</li> <li>automatic fan switch</li> </ul> Standard outfit: <ul> <li>6 metal coated shelves</li> <li>(dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> </ul> Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>						
<ul> <li>door lock</li> <li>automatic fan switch</li> <li>Standard outfit: <ul> <li>6 metal coated shelves</li> <li>(dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> </ul> </li> <li>Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> </li> <li>Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul> </li> </ul>						
<ul> <li>automatic fan switch</li> <li>Standard outfit: <ul> <li>6 metal coated shelves</li> <li>(dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> </ul> </li> <li>Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> </li> <li>Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul> </li> </ul>						
<ul> <li>6 metal coated shelves (dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> <li>Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> </li> <li>Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul> </li> </ul>						
<ul> <li>6 metal coated shelves (dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> <li>Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> </li> <li>Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul> </li> </ul>						
<ul> <li>(dimension of shelf: 530 x 650 mm)</li> <li>12 shelf guides</li> <li>manual description</li> <li>Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> </li> <li>Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul> </li> </ul>	Standard out	fit:				
<ul> <li>12 shelf guides</li> <li>manual description</li> <li>Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> </li> <li>Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul> </li> </ul>	- 6 metal coated shelves					
<ul> <li>manual description</li> <li>Optional outfit: <ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> </li> <li>Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul> </li> </ul>	(dimension of shelf: 530 x 650 mm)					
Optional outfit: - additional metal coated shelves - shelf made of INOX - hooks for meat products - sound signalling - foot pedal for door opening - inside light - temperature recorder Optional execution: - static air circulation - another finishing materials for example AISI 430	- 12 shelf guides					
<ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>	- manual description					
<ul> <li>additional metal coated shelves</li> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>						
<ul> <li>shelf made of INOX</li> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>	•					
<ul> <li>hooks for meat products</li> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>						
<ul> <li>sound signalling</li> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>						
<ul> <li>foot pedal for door opening</li> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>						
<ul> <li>inside light</li> <li>temperature recorder</li> </ul> Optional execution: <ul> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>	0 0					
<ul> <li>temperature recorder</li> <li>Optional execution:</li> <li>static air circulation</li> <li>another finishing materials for example AISI 430</li> </ul>						
Optional execution: - static air circulation - another finishing materials for example AISI 430	Ŭ					
- static air circulation - another finishing materials for example AISI 430	- temperature	recorder				
- static air circulation - another finishing materials for example AISI 430	Optional ever	cution:				
- another finishing materials for example AISI 430	-					